

**Republic of the Philippines  
SENATE  
REQUEST FOR SEALED QUOTATION**

Date : 7/20/2022  
 RSQ No. : E22-07-008  
 Requisitioner : PRIB  
 Canvasser : CHRISTIAN S. FELAGIO

Sir/Madam:

We invite all GEPS registered bidders to submit sealed quotation for the item/s listed below, addressed to the Chairman, Bids and Awards Committee (BAC), 4/F Senate of the Philippines, GSIS Bldg., Financial Center, Pasay City. The quotation for Purchase Request No. **PR-22-07-621** must be submitted to the Office of the Chairman, Bids and Awards Committee, Room 408 or the Secretariat, Bids and Awards Committee, Room 401, 4/F Senate of the Philippines, GSIS Building, Financial Center, Pasay City, not later than 5P.M. of                     . Kindly observe and comply with the stated specifications / descriptions / unit of items for quotation, and specify country of manufacture or origin in the item, any erasure must be properly initialed by the bidder. Bidders are presumed to have reviewed all bids indicated herein before submission to the BAC. Please do not forget to indicate the following references in your envelope "PR NO.                      / RSQ NO.                     , Assigned Canvasser:                     , CLOSING DATE:                     "

LIKewise, ALL QUOTATIONS MUST BE VALID FOR AT LEAST THIRTY (30) DAYS FROM THE CLOSING DATE OF POSTING WITH THE PhilGEPS AND SUBJECT TO THE GENERAL CONDITIONS FOUND AT THE BACK OF THIS FORM.

*[Signature]*  
**ATTY. MARIA VALENTINA S. CRUZ**  
 CHAIRPERSON  
 BIDS AND AWARDS COMMITTEE

**THE CHAIRMAN**  
 Bids and Awards Committee  
 c/o Secretariat, Bids and Awards Committee  
 Room 401 4/L, Senate of the Philippines, GSIS Building, Financial Center, Pasay City  
 Fax No. 552-6601 local 1602 or 552-6803

Sir: As requested in your letter above, we are pleased to quote hereunder our price/s for the following item/s subject to the General Conditions stated at the back:

Item No	Quantity	UOM	Item Description	Unit Cost	UNIT PRICE (Inclusive of all Taxes)	TOTAL
PR-22-07-621 - PRIB						
1	4	UNIT	HDMI to SDI converter (please see attached specifications)	<b>84,000.00</b> 21,000.00/UNIT		
2	5	UNIT	SDI to HDMI converter (please see attached specifications)	<b>65,000.00</b> 13,000.00/UNIT		
3	12	UNIT	HDMI Distribution Amplifier (please see attached specifications)	<b>174,000.00</b> 14,500.00/UNIT		
4	4	UNIT	AUDIO VIDEO DISTRIBUTION AMPLIFIER (please see attached specifications)	<b>296,000.00</b> 74,000.00/UNIT		

----- NOTHING FOLLOWS -----

**RECEIVED**

JUL 20 2022  
 BY:                      TIME: 3:10  
 PROCUREMENT, PPS

(QUOTATIONS must be valid for at least thirty [30] to forty five [45] days from closing date)

**TERMS OF DELIVERY** \_\_\_\_\_

**TERM/S OF PAYMENT:** Government Terms (NO C.O.D. / NO ADVANCE PAYMENT) \_\_\_\_\_

**Address of Supplier** \_\_\_\_\_ **(Name of Company)** \_\_\_\_\_

**E-Mail Address** \_\_\_\_\_ **PhilGEPS Reg. No.** \_\_\_\_\_ **Expiry Date:** \_\_\_\_\_

**Tel./Fax No./s** \_\_\_\_\_

**TIN** \_\_\_\_\_ **(Signature over Printed Name Authorized Representative)** \_\_\_\_\_

**GEPS REF#** 886 9013  
**Closing Date:** AUGUST 31, 2022  
**By:** CSF  
**Date Posted:** JULY 23, 2022

**SDI to HDMI Converter**

**Specifications:**

Heavy Duty
Broadcast Quality
Portable
3G/HD/SD-SDI to HDMI Converter with Audio Embedder
Selectable YPbPr or RGB colorspace and HDMI/DVI output modes
Full 5.1 channel audio conversion to HDMI audio with selectable C/LFE line-up control.
Audio de-embed of selected group 1/2 pair to analog audio output pair.
SDI input copy output allows converter to provide SDI pass-thru
Standards Supported: SMPTE 259M, 292M, 424M (10-bit video processing)
Video Inputs - SDI (75Ω BNC) - DC power (via USB or adapter)
Video Outputs - HDMI (HDMI 1.4 compliant). HDMI output can be set as DVI-D (limited to SMPTE HD formats). 1080p at 29.97/30/50/59.94/60 fps 1080i 50/59.94/60 fps 720p 50/59.94/60 fps 576i / 625 lines 50 fps 480i / 525 lines 59.94 fps - SDI reclocked input copy (75Ω BNC) - (2) analog audio (unbalanced consumer RCA)
Audio Conversion Format 48 kHz sampling, 24-bit SDI groups 1/2 to HDMI Ch 1-8 (with user-selectable C/LFE line-up)
Power Source: Powers directly from host equipment USB or standard corded power adapter. USB power and corded adapter can be simultaneously used to provide redundant power sourcing. Power DC: 5-16 VDC Power Consumption: 2.4 W DC Power Connectors: USB Mini and coaxial locking connector (for use with supplied power adapter) Operating Temperature Range : -4°F to 158°F, (-20°C to 70°C)
Dimensions (WxHxD) : 5.5" x 3" x 1" (including connector projections); (139 x 77 x 26 mm)

**Please attached product manual and pictures for evaluation purposes.**

**Product demo and testing is required upon delivery of item/s.**

COUNTRY OF ORIGIN: US

PAYMENT : per government payment system

WARRANTY : 1 year warranty

DELIVERY PERIOD : 30 calendar days upon receipt of P.O.

NOTED BY:

RAYMUNDO R. CORRO  
BUREAU DIRECTOR  
PUBLIC RELATIONS & INFO. BUREAU

*[Handwritten signature]*

ESTUPIDAN, EB

NEW SPECIFICATIONS  
15 June 21, 2022

DESCRIPTION
<b>HDMI to SDI Converter</b>
<b>Specifications</b>
Heavy Duty
Broadcast Quality
Portable
HDMI to 3G/HD/SD-SDI Converter with Audio Embedder
Direct conversion from HDMI to SMPTE 259M, 292M and 424M SDI. Accepts DVI-D input sources with conversion to coax SDI.
5.1-channel embedding from HDMI audio. Stereo analog audio embedding from stereo analog audio input pair.
2x SDI DA output
Standards Supported: SMPTE 259M, 292M, 424M
<b>Video Inputs</b>
HDMI (HDMI 1.4a compliant). DVI-D compliant input (limited to SMPTE HD formats).
1080p at 29.97/30/50/59.94/60 fps
1080i 50/59.94/60 fps
720p 50/59.94/60 fps
576i / 625 lines 50 fps
480i / 525 lines 59.94 fps
<b>Audio Conversion Format</b>
48 kHz sampling, 24-bit
8-Ch HDMI to SDI groups 1 and 2
Power Source: Powers directly from host equipment USB or standard corded power adapter. USB power and corded adapter can be simultaneously used to provide redundant power sourcing.
Power DC: 5-16 VDC
Power Consumption: 2.4 W
DC Power Connectors: USB Mini and coaxial locking connector (for use with supplied power)
1 x USB Mini-B (5 to 16 VDC) Input
1 x Barrel (5 to 16 VDC) Input
Operating Temperature Range : -4°F to 158°F, (-20°C to 70°C)
Dimensions (WxHxD) : 5.5" x 3" x 1" (including connector projections); (139 x 77 x 26 mm)

**Please attached product manual and pictures for evaluation purposes.**

**Product demo and testing is required upon delivery of item/s.**

COUNTRY OF ORIGIN: US

PAYMENT : per government payment system

WARRANTY : 1 year warranty

DELIVERY PERIOD : 30 calendar days upon receipt of P.O.

NOTED BY:

RAYMUNDO R. CORRO  
BUREAU DIRECTOR  
PUBLIC RELATIONS & INFO. BUREAU

ESTUARICEN EIB



as of June 21, 2022

**DESCRIPTION**

**HDMI Distribution Amplifier/Splitter**

**Specifications**

Heavy Duty  
 Broadcast Quality  
 Portable  
 12G/6G/3G/HD/SD-SDI / ASI / MADI Reclocking Distribution Amplifier  
 Six 12G/6G/3G/HD/SD equalized and reclocked outputs  
 1x4 ASI distribution capability  
 with Input status LED indicator  
 SMPTE 2082-1/424M/292M/259M Auto-Reclock  
 1 x 6 Distribution Amplifier  
 Number of DA outputs: 6  
 Signal Level: 800 mV +/- 10%  
 DC Offset: 0.0V +/- 0.5V  
 Rugged construction backed with a five-year warranty  
 12G/6G/3G/HD/SD-SDI / ASI / MADI Inputs  
 Number of inputs: 1  
 Impedance: 75Ω  
 SDI Formats Supported: SMPTE 2082-1, 424M, 292M, 259M  
 Other Formats Supported: ASI, MADI  
 Power : <2 Watts  
 Power DC: 5-16 VDC  
 Operating Temperature Range : -4°F to 158°F, (-20°C to 70°C)  
 Box Dimensions (LxWxH) : 14.7 x 10.8 x 3"

**Please attached product manual and pictures for evaluation purposes.**

**Product demo and testing is required upon delivery of item/s.**



COUNTRY OF ORIGIN: US

PAYMENT : per government payment system

WARRANTY : 1 year warranty


DELIVERY PERIOD : 30 calendar days upon receipt of P.O.

NOTED BY: 

RAYMUNDO R. CORRO   
 BUREAU DIRECTOR  
 PUBLIC RELATIONS & INFO. BUREAU 

New

June 21, 2022

  
 ESTUARDO, EVIS

**AUDIO VIDEO DISTRIBUTION AMPLIFIER****SPECIFICATIONS:**

Specifications: High Quality, Heavy Duty and with 2.7 inch TFT LCD Monitor  
14-channel distribution amplifier (one HDMI input, one 3G-SDI input, twelve  
3G-SDI outputs, and two HDMI outputs)

Data Input: SDI Video Input: SD/HD/3G-SDI (BNC 75Ω) x1 HDMI Video Input:  
SD/HD/3G (HDMI Type A) x1

Data Output: SDI Video Output: SD/HD/3G-SDI (BNC 75Ω) x12 HDMI Video  
Output: SD/HD/3G (HDMI Type A) x2

Video Formats: 720x480i@59.94/60, 720x576i@50, 1280x720p@50/59.94/60,  
1920x1080i@50/59.94/60, 1920x1080p@23.94/24/25/29.97/30,  
1920x1080p@50/59.94/60

Audio I/O: XLR (Female) x2 and XLR (Male) x2

Display: 2.7 inch TFT LCD: Input Video Display (SDI or HDMI), AUDIO Level  
Meter Display, Input Video Resolution Display

Power Input: 100 to 240 VAC at 50/60 Hz

With AC power cord


DELIVERY: Sixty (60) Calendar days upon receipt of Purchase Order

VALIDITY: One (1) month from date of quotation

WARRANTY: One (1) year warranty on parts and labor

PRICE BASIS: Delivered VAT Inclusive

PAYMENT: per government payment system

  
RAYMUNDO R. CORRO  
BUREAU DIRECTOR  
PUBLIC RELATIONS & INFO. BUREAU